



BAMBOO EVOLUTIONS™

PHYSICAL PROPERTIES

| | |
|-------------------|---|
| Description 1 | Moso6™ Solid Locking Strand Woven Bamboo |
| Species | Moso6™ Premium 6-Year Mature; Moso Bamboo |
| Description 2 | Moso6™ Solid Locking Corboo™ |
| Species | Moso6™ Premium 6-Year Mature; Moso Bamboo infused with Cork |
| Size | Planks: 5.25" x 72" x 0.5" Multi Width Planks: (5.43", 3.62", 2.43") x 72.75 x .0.5" |
| Installation | Glue-less Floating or Glue-Down |
| Profile | Drop and Lock |
| Edge | Micro-beveled edge - slight .2mm eased edge |
| Colors | Natural |
| Finish | Endura AR+™ Commercial wear layer Sealed and cured backs of the plank |
| Packaging | 21.27 sq. ft. /carton, 55 lbs. 23.25 sq. ft. /carton, 64 lbs. (multi-width) |
| Country of Origin | Manufactured in China |

HEALTH AND SAFETY

| | |
|-----------------------|--|
| Flammability | ATSM E 662-97 Passes NBS Smoke Chamber |
| Critical Radiant Flux | ASTM E 648 Class 1 |
| Slip Resistance | ASTM C1028 dry: 0.78 Wet: 0.59 |
| IAQ | GREENGUARD GOLD Certification CARB2012 CA-CHPS |

PERFORMANCE

| | |
|-----------------------|---|
| Density Impact | ASTM 1037 +2700 |
| Abrasion Resistance | ASTM-D4060 Taber Abrasion: Initial Wear Through: >1000 cycles |
| Dimensional Tolerance | .0075% I N/A w |
| Moisture Content | ASTM D 4442 >6 to <9% |
| Warranty | 15-year commercial - Lifetime structural |

SUSTAINABLE ATTRIBUTES:

- Rapidly Renewable Resource
- Low-Emitting Materials