



LEED Product Data Sheet

Project:

Date:

Location:

Name of Product/Material: Natural Bamboo Basics SL™

Description: Engineered strand bamboo planks
 Manufacturer: USFloors Inc.- USFContract

Product/Material Cost: \$

Recycled Content:

Pre-Consumer: Post-Consumer: %

Regional Qualifications for Product/Material

Location of Manufacture of Bamboo Planks*: China
 Distance from Project Site:

List of Material Components used in Manufacturing Process

Component: Strand Woven Bamboo
 Component Location: China
 Distance from Project Site: miles
 Percentage, by Weight: 97.00%

Component: Adhesive
 Component Location: China
 Percentage, by Weight: 1.75%

Component: UV Cured Acrylic - Endura AR+
 Component Location: Dalton, GA
 Distance from Project Site: miles
 Percentage, by Weight: 1 %

Component: UV Cured Aluminum Oxide [back]
 Component Location: China
 Distance from Project Site: miles
 Percentage, by Weight: .25 %

Low Emitting Materials%

No Adhesive Used if installing as a Drop Lock Floor
 Adhesive Use: USFloors 30GU35 (SCAQMD) Rule # 1168 X EQ

Flooring Systems:
 Adhesive: Green Guard Indoor Air Quality Certified Yes X No ___
 Flooring: GREENGUARD™ Gold Certified Yes X No ___

Rapidly Renewable Material

Yes X No ___ Percent Renewable: 97.00 % Cost: \$ ___ X MR

Certified Wood

Percent Certified: _____ %
 FSC Chain of Custody Certificate Number: _____ MR

This Information has been provided by:

Name: Gary Keeble, Jr. LEED AP
 Company: USFloors Inc

Date: 10/18/2012

The information on this data sheet represents accurate and reliable data to the best of our knowledge and belief.
 *Manufacture is defined as the assembly of the final product not including on-site assembly or installation