



Citadel Collection Specification

PHYSICAL PROPERTIES

Species	European White Oak		
Construction:	Engineered T&G Wide Plank Oak Flooring with soft wood fillets and stabilizer sheet		
Thickness	15mm - 5/8" 4mm Oak wear layer		
Moisture	> 6 :< 9		
Finish:	Natural-E™ Natural Oil Finish		
Installation:	Glue, Nail, Float		
Sizes:			
	FORTRESS SERIES	7-1/2" x 75" x 5/8"	31.11 sq. ft. /carton, 65 lbs.
	BASTIAN SERIES	7-1/2" x 72" x 5/8"	31.11 sq. ft. /carton, 65 lbs.
	Rochester	7-1/2" x 75" x 5/8"	29.82 sq. ft. /carton, 70 lbs.
	TOWER SERIES	8 1/2" x 86 5/8" x 5/8"	24.63 sq. ft. /carton, 62 lbs.
	TRAVERSE SERIES	7-1/2" x 75" x 5/8"	31.11 sq. ft. /carton, 65 lbs.

Each package contains one plank cut in half for use on starter row.

HEALTH AND SAFETY

Flammability:	ASTM E84 Class C
Smoke:	ASTM E 662-05 <450 Passes
Radiant Panel	ASTM E648-06 Class 1 rating as specified in NFPA Life Safety Code 101 and IBC 804.2
Moisture	> 6 :< 9
IAQ	CARB Compliant

PERFORMANCE

Warranty	15-Year Commercial Warranty Lifetime Structure Warranty
Certification	Lacey Act Compliant
Country of Origin	China
Sustainable Attributes	MR Certified Materials EQ - NAUF Compliant EQ Low-Emitting adhesives for USFloors Adhesive

Environmental Statement: USFloors' commitment is to provide consumers and specifiers with beautiful a durable floors at a good value, while minimizing our impact on the environment and enhancing and improving it whenever possible. USFloors is a member of the USGBC.