



LEED® Product Data Sheet

Project: _____ **Date:** _____
Location: _____

Name of Product/Material: Citadel Collection
 Manufacturer: USFloors Inc.- USFContract
 Description: engineered oak wide plank with oil finish
 15mm x 189 mm x 1830 mm 5/8" x 7 1/2" x 75"
 Product/Material Cost: \$

List of Material Components used in Manufacturing Process

Component: white oak Component Location: Eastern /Western Europe Distance from Project Site: Percentage, by Weight: 28%	Component: fir fillets/ poplar ply Component Location: China Distance from Project Site: Percentage, by Weight: 65.4%
Component: adhesive Component Location: China Distance from Project Site: Percentage, by Weight: 6.0%	Component: oil Component Location: Denmark Distance from Project Site: Percentage, by Weight: 0.6 %

Low Emitting Materials - EQ

Flooring Materials: NAUF compliant
 CARB2 compliant

Low Emitting Materials - EQ

Adhesive:30GU35
 USFloors/USFContract Wood Adhesive - GREENGUARD Certified
 30GU35 is a solvent free and isocyanate free, with negligible VOC content, contains no hazardous chemicals as per OSHA Regulation CFR 1910.1200
 Passes SCAQMD Rule # 116

This Information has been provided by:

Name: Gary Keeble, Jr. LEED AP Date: 06-22-15
 Company: USFloors Inc
 *Manufacture is defined as the assembly of the final product not including on-site assembly or installation
 Contribution opportunities based on USGBC LEED V4 [2009]