



The Commercial Division of USFloors Inc.
3580 Corporate Drive, Dalton Georgia
877-292-4044 www.usfcontract.com

Midtown Revival Collection Specification

PHYSICAL PROPERTIES

Species	European White Oak
Construction:	Engineered T&G Wide Plank Oak Flooring With solid oak layer over 3-ply construction
Thickness	12mm - 1/2" 2mm Oak wear layer
Moisture	> 6 to < 9 %
Finish:	Oil Finish
Installation:	Glue, Nail, Float
Size:	7-1/2" x 75" x 1/2" (34.97 sq. ft./carton) 7-1/2" x 75" x 1/2" (31.09 sq. ft./carton)

Each package contains one plank cut in half for use on starter row.

HEALTH AND SAFETY

Flammability:	ASTM E84 Class C
Smoke:	Pending
Radiant Panel	Pending
Moisture	> 6 to < 9 %
IAQ	CARB2 Compliant

PERFORMANCE

Warranty	10-Year Commercial Warranty Lifetime Structure Warranty
Certification	Lacey Act Compliant
Sustainable Attributes	EQ - NAUF Compliant EQ Low-Emitting adhesives for USFloors Adhesive

Environmental Statement: USFloors' commitment is to provide consumers and specifiers with beautiful a durable floors at a good value, while minimizing our impact on the environment and enhancing and improving it whenever possible. USFloors is a member of the USGBC.