

## Avignon Corsica

## Technical Specifications

<b>Description:</b>	<b>FSC certified Wide Plank Oak Flooring with natural oil finish</b>
<b>Species:</b>	<b>Northern European Oak</b>
<b>Warranty:</b>	<b>Heavy Commercial - Lifetime structural warranty</b>
<b>Installation:</b>	<b>Glue-down, Nailed or Stapled</b>
<b>Sizes:</b>	<b>10 ¼" x 86 5/8"</b>
<b>Thickness:</b>	<b>21mm [6mm wearlayer]</b>
<b>Finish:</b>	<b>Clean Visual</b> <b>NATURAL-E™ Organic natural oil finish</b>
<b>Colors:</b>	<b>Clear AVC-2006</b> <b>Shadow AVC-2015</b> <b>Custom colors available</b>
<b>VOC Emissions:</b>	<b>Proprietary resin adhesive used in manufacturing, the formaldehyde emission exceeds E0 standard, no urea formaldehyde, no halogenated hydrocarbons, herbicides, heavy metals and any harmful emissions</b>
<b>Slip Resistance:</b>	<b>ADA and OSHA compliant</b> <b>.86 Dry, .85 wet [ASTM D 2394]</b>
<b>Moisture Content:</b>	<b>&gt; 6 to &lt; 9% [ASTM D 4442]</b>
<b>Certified Manufacturing:</b>	<b>ISO 9001</b> <b>CARB2012</b> <b>Lacey Act Compliance</b>
<b>Green Build Statement:</b>	<b>Natural Bamboo floors contribute to satisfying LEED credits for Rapidly Renewable Resources [MR] and Low Emitting Materials [EQ] under the LEED Rating System. The determining factor for indoor air quality is the quantity of noxious emanations from volatile organic compounds in adhesives and finishes. Natural Bamboo® Strand Woven Solid can also contribute to attaining points within the Environmental Quality section of the LEED Rating Systems as it uses adhesives that meet the SCAQMD rule #1168 and it contains no added urea-formaldehyde, as required by LEED. The LEED (Leadership in Energy and Environmental Design) Green Building Rating System is the nationally accepted benchmark for the design, construction, and operation of high performance green buildings as administered by U.S. Green Building Council. USFloors is a member of the USGBC.</b>